



INSTALLATION INSTRUCTIONS

For detailed installation instructions follow the directions provided by the manufacturers of the adhesives listed below. For the optimum color blend and pattern, a dry layout is highly recommended. Hive tiles can be installed with or without grout.

We recommend the adhesives listed below or equivalents having the same physical/mechanical properties.

LATICRETE LATAPOXY 310 STONE ADHESIVE LATICRETE LATAPOXY 300 STONE ADHESIVE BOSTIC GRIP N' GRAB

PRECAUTIONS:

- Products are intended as a veneer covering only for vertical surfaces.
- · High heat may change the properties of this product.

TEST RESULTS	ASTM TEST	HIVE
FSI (flame spread index)	E84	5 (A CLASS)
Absorption by weight %	C97	0.07%
Density & bulk specific gravity	C97	2583 kg./m³
Linear thermal expansion	C372	25.5609 x 10-6
Bond strength	C482	827PSI
Freeze/Thaw resistance	C666	0.1% weight
Rupture modulus	C99	16.1 MPa
Compressive strength	C170	76.2 MPa
Abrasion index	C241	9.2
Knoop hardness	C849	1259 Mpa
Flexural strength	C880	16.6 MPa
Volatile organic compunds (VOC)emissions	CA01350	Compliant
Resistance to salt corrosion using S02 (PH<3)	Din 50021 class	Compliant
Ageing due to chemical-physical erosion	NF T30 049	Compliant

All technical information provided herein has been provided by the manufacturer of the product. Realstone Systems, L.L.C. has relied on the manufacturer for this technical information and Realstone Systems, L.L.C. does not warrant the accuracy of any technical information provided in this brochure. Realstone Systems, L.L.C. cannot be held liable in any cause of action and makes no expressed or implied warranty of the material herein.

http://www.petrastoneitalia.com/contatti_eng.htm.Petrastone shall not be deemed responsible for any issue which may arise from non-standard installations if not contacted beforehand.